



ALTV244

Overview

ALTV244 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 0.9 amp.

Output:

- Four (4) fuse protected outputs.
- 24VAC @ 4 amp (100VA) supply current
(1 amp per device, 3.5 amp max.)
- or 28VAC @ 3.5 amp (100VA) supply current
(0.875 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 49.13 BTU/Hr.
 - 28VAC: 50.16 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 103.5VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
- Product weight (approx.): 6.2 lbs. (2.8 kg.).
- Shipping weight (approx.): 6.8 lbs. (3.1 kg.).

Agency Approvals



Enclosure Dimensions (H x W x D approximate):
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

