

NetWayXT - PoE Repeater



Overview

NetWayXT repeater modules interface with NetWay midspans to extend data (video) 100m. NetWayXT is PoE, IEEE 802.3af (15W) compliant. A maximum range of more than 600m is possible using multiple repeaters, based on camera/ device port requirement.

Port Status

LEDs

Structured Cable to

PoE Camera/

Device or next NetWayXT



Specifications Data: Mechanical: • Extends data 100m. • Lightweight molded compact insulated housing. • Dimensions (W x D x H approx.): Power: 2.5" x 3.8" x 1" (63.5mm x 96.52mm x 25.4mm) • IEEE 802.3af (15W) compliant. • Product weight (approx.): 0.2 lbs. (0.1 kg). Features: • Shipping weight (approx.): 0.25 lbs. (0.11 kg). • Port status LED. Electrical: • Operating temperature: 0° C to 49° C ambient. Agency Approvals UL/CUL Listed for Information () European Conformity **US** Technology Equipment (UL 60950-1). **Typical Application:** (\mathbf{f}) Structured Cable from NetWay1, NetWay8, NetWay8M, NetWay16, NetWay16M or last NetWayXT Power LISTED LED I.T.E. 43KC NetwayXT Repeater

(F

IN

www.altronix.com

Power

0UT