



Model	LS-9604PD
<b>System</b>	
Main Processor	ARM Cortex A9 Processor
Operating System	Embedded LINUX
<b>Video</b>	
Input	4 Channel, BNC (1.0 Vp-p,75Ω)
Output	1 TV, 1 VGA
<b>Audio</b>	
Input	2 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel
Trigger Events	Recording, Email
Email Alarm	Send Strings to The Designated E-mail
<b>PTZ</b>	
Interface	NO
Protocol	NO
Baud Rate	NO
Address	NO
<b>Display</b>	
TV	BNC (1.0 Vp-p,75Ω), Resolution: PAL:704×576, NTSC: 720×480
VGA	Resolution: 800×600, 1024×768, 1280×720, 1280×1024, 1920×1080
HDMI	NO
Display Split	4 Channel / 1Channel
Privacy Masking	4 Rectangular Zones (Each camera)
OSD	Camera Title, Time, Video Loss, Motion Detection, Recording
<b>Recording</b>	
Video Compression	H.264
Audio Compression	ADPCM
Resolution	PAL: 960H(960×576), D1(704×576), CIF(352×288) NTSC: 960H(960×480) D1(720×480), CIF(352×240)
Video Quality	Best/Fine/Normal
Record Rate	PAL : 960H@100fps, D1@100fps, CIF@100fps NTSC: 960H@120fps, D1@120fps, CIF@120fps
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Local Sync Playback	4 Channel / 1Channel
Remote Sync Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network (Support back up to AVI directly)
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DHCP, DNS, DDNS
Web Browser	IE6-11, Firefox, Chrome (Under Windows System)
CMS Software	Support Windows XP /Windows Vista/Windows 7/Windows 8
Extra Stream	CIF/QCIF(1~25fps)
Smart Phone	iPhone, iPad, Android, Andriod Pad
<b>Hard Disk Driver</b>	
Interface Type	1 SATA Interface
Capacity	Up to 4TB Capacity
<b>General</b>	
Language	English, Italian,Greek, Russian, Polish, Portuguese, Turkish, Hungrain,Spanish, French German Japanese,Slonakia,Vietnam, Simple Chinese, Traditional Chinese
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/2A
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	215mm×215mm×53mm
Weight	2KG (Without HDD)