



LPTM12XCG

Product Description

Specification:

Vandalproof High Speed Dome Camera

Pan range: 0° ~360° Continue

Tilt range: 0° ~90° Flip

Pan Speed: Max 80° /sec

Preset: 16

Weatherproof Outdoor IP66

RS485, Pelco D/P supported

Size: 121 x 177mm

Weight: 3.0Kg



Model	LPTM12XCG	LPTM10XSG
Pick up Elements	1/3" SUPPER HAD IIColor Sony CCD	1/4" SUPPER HAD IIColor Sony CCD
Effective picture Elements (H×V)	NTSC: 768(H)×494(H) PAL: 752(H)×582(V)	NTSC: 768(H)×494(H) PAL: 752(H)×582(V)
Horizontal Resolution	700TV Line	500TV Line
Minimum Illumination	0.001 Lux	0.001 Lux
S/N Ratio	50dB	50dB
Scanning System	2:1 interface	2:1 interface
Synchronous System	Internal, Negative Sync	Internal, Negative Sync
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/100,000s	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/100,000s
Gama Characteristic	0.45	0.45
Video Output	1Vpp, 75Ω	1Vpp, 75Ω
Auto Gain Control	Auto	Auto
Power/Current	DC12V(+/-10%)/800mA	DC12V(+/-10%)/800mA
Lens	5-60 mm Dynamic Varifocal Lens	3.8-38 mm Dynamic Varifocal Lens
Dimension(mm)	121×177(H)	121×177(H)
Weight(g)	2800	2800
Storage Temperature	-30~+60C RH95% MAX	-30~+60C RH95% MAX
Operating Temperature	-10~+50C RH95% MAX	-10~+50C RH95% MAX