

XVAULT XNVR300

Professional Level 2U 12 Bay Rackmount Network Video Recorder

250-350 Mbps of Throughput

The xVault xNVR300 Series are enterprise network video recorders engineered for mid to large scale surveillance deployments that require exceptional throughput performance. The xNVR300 Series is fully customizable with a wide range of options including processor, memory, storage, and optical drive. Supporting the Intel® Xeon® Processor E5 Series, this system is armed with xVault Unified Storage technology with capability to hold up to 72TB of maximum raw storage. Additional storage expansion shelf options are available to meet additional storage demands.



The xNVR300 product line is built based on an open platform system delivering multiple benefit for larger scale deployments including:

- Fully customizable with a wide range of options
- Up to 72TB of maximum raw storage
- Alternative solutions to meet projects needs so our customers will not get locked into preconfigured solutions
- Product design and development with the ability to be targeted to specific performance or project scenarios
- · Application flexibility with the ability to tune to specific metrics and view high demand analytics



Our Flagship Surveillance Deployments with Exceptional Throughput Performance

- Intel[®] Xeon[®] Processor F5
- Up to 72TB of maximum raw storage
- 12 × 3.5" hot-swappable drives



XVAULT XNVR300

2U 12 BAY RACKMOUNT

SYSTEM

Processor	Intel® Xeon® Processor E5 Series
Operating System	Windows Server® 2012 R2 Windows Server® 2008 R2 Windows 7 Embedded Enterprise
Memory	Up to 64GB DDR4 2133MHz ECC Registered
Maximum Raw Storage	72TB
Optical Drive	N/A
HDD Tray	Hot-Swappable
Networking	2 × 1GbE LAN Ports Standard Up to 6 × 1Gb LAN Ports Up to 1 × 10Gb LAN Port
Rear I/O	$2 \times$ USB 3.0, $2 \times$ USB 2.0, $1 \times$ PS/2 Combo, $1 \times$ VGA, $1 \times$ MGMT LAN
OS RAID	RAID 1
RAID Level Support Options	0, 1, 5, 6, 10, 50, 60, JBOD
NVR Hardware Monitoring	Pre-installed with Seneca xConnect Health Monitoring Software
Warranty	3 Year, Next Day, Onsite Server Warranty

Form Factor	2U
OS Drive Bays	2×2.5"
Data Drive Bays	12 × 3.5" Hot-Swappable
Video Outputs	2×DVI/VGA
Power Supply	800W / 100 ~ 240V Redundant
AC Input VAC Freq	47 ~ 63 Hz
Ambient Operating Temp	0°C (32°F) ~ 35°C (95°F)
Operating Humidity	5% ~ 95% non-condensing
Dimensions (w x h x d)	$19 \times 3.5 \times 27.5$ inches / $483 \times 89 \times 700$ millimeters

 $^{^{\}star}$ RAID Level configuration to be specified at time of order











